

19000A-LED

4" IC Airtight New Construction LED Housing with Molex Connector

Product Description

The 19000A-LED features molex connections that allows for quick, snap-in connection of NICOR® D-series LED downlights. Suitable for new construction in residential and commercial applications. IC rated. Suitable for direct contact with insulation.

Housing

Airtight housing limits the exchange of air between ceiling plenum and heated/cooled areas
Washington State Energy Code approved to meet restricted airflow requirements
5 1/2" height allows use in 2" x 6" joist construction

Plaster Frame

Housing is secured to plaster frame with screws and can be removed for access to junction box
Housing adjusts from 1/2" to 1 1/2" to accommodate ceiling thickness

Junction Box

Listed for through branch circuit wiring and includes several 3/4" knockouts
Four pryouts with integral strain relief simplify Romex installation
Supplied with three push-in wire connectors

Hanger Bars

Heavy-gauge NICOR captive hanger bars provide greater stability, allowing housing to be positioned at any point within a 24" joist span, then locked in place with set screws
Unique hanger bar lip design helps align can to joist
Four double-headed captive nails provide for ease of installation
Bars can be repositioned 90° on plaster frame without tools
Bars fit onto T-bar spine for quick alignment and can be permanently secured
Score lines allow bars to be shortened without tools to accommodate a 12" joist span

Ordering Information

Catalog Number	Description
19000A-LED	4" IC Airtight New Construction LED Housing with Molex Connector

Project

Catalog

Type



Molex Connector

