

20344-120 - 277V

Linear Fluorescent 4 Lamp Highbay

Product Description

This T5HO high-bay four-lamp, fluorescent fixture offers an affordable solution as a point-for-point replacement of 250W and 400W HID high-bays. It's perfect a perfect choice for high mounting height requirements in industrial or retail applications. This 120/277V high bay delivers instant start and instant re-strike as well as a high CRI. It also includes a wire guard.

Construction

- Die-formed heavy 20 gauge steel housing construction.
- Riveted end plates increase housing rigidity and integrity.
- Multiple vents aid lamp/ballast heat dissipation.
- Two access doors with captive knurled screws for tool-less entry open 180° to expose attached ballasts.

Optical System

Die-formed aluminum (G320) reflector designed for maximum 86% reflectivity. Secured to housing with fasteners.

Electrical

- Class P, 60Hz high-power factor ballasts. Ballast factor of 1.15
- Universal 120-277V ballast.
- Includes IDEAL® PowerPlug™ which complies with NEC 410.73(G) and CEC 30-308(4) requirements during ballast disconnect for maintenance safety and reduced service disruption.
- Terminal blocks facilitate secure connections between ballasts and supply wiring.
- Pressure-lock lamp holders for secure lamp installation.

Installation

Includes heavy-gauge chain mounting kit.
Lamps not included.

Ordering Information

Model	Description
20344-120-277V	Linear Fluorescent 4 Lamp Highbay
Also available:	
20344-120-277V-4100K	Linear Fluorescent 4 Lamp Highbay (Includes Lamps)

Options

Model
Occupancy Sensor
Wire Guard
6' power cord and plug 347-480V and 4100K

Project

Catalog

Type

