

# Installation Instructions

SAVE THESE INSTRUCTIONS FOR FUTURE REFERENCE

**Model#: 34031**

**Lamp Replacement: All wattage of compact fluorescent lamps**

## **WARNING**

- ☒ Installation must be performed by a qualified licensed electrician
- ☒ Before installation, turn off the main power at the circuit breaker

## **CAUTION:**

- ☒ Use safety precautions. Always handle lamp by its base
- ☒ To prevent electric shock, do not insert any objects through openings or attempt to open the adapter

## **NOTE:**

- ☒ Take the fixture and the screw pack from the box, make sure that no parts are missing by referencing the illustrations on the installation diagram

## **FIXTURE INSTALLATION:**

- 1) Turn off main power at circuit breaker before attempting to install luminaries.
- 2) Tightened the crossbar to the junction box using the 2 screws provided. Pull the existing electrical wires out of the box.
- 3) Connect the supply leads from the electrical outlet box to the fixture wire leads using the wire nuts provided in your screw pack as per the diagram. Make sure the “black lead” from the fixture goes to the “black supply lead”, and the “white lead” from the fixture goes to the “white supply lead”. Thread wires to green ground screw.
- 4) Place the fixture against the wall to have the mounting threaded screw passing through the crossbar. Tighten it with the cap nuts provided.
- 5) Screw on GU24 base compact fluorescent lamp into the socket. Hold the lamp by its base, insert the pins into the 2 curved slots of the lamp socket and twist clockwise until the lamp is locked in.
- 6) Restore power to the electrical outlet box to make sure your fixture is working properly.



