

NICOR[®] | LED

NUC-3 LED Under Cabinet



Now dimmable, offering you more flexibility

90+ CRI

Greater than 90 CRI, makes colors more vibrant and accurate.



Dimmable

Dimmable with most Triac dimmers.



Longer Life

High performing CREE[®] LEDs have a >60,000 hour lifetime



NUC-3

LED Under Cabinet

The NUC-3 LED under cabinet is an energy efficient lighting solution that is not only affordable, but now offers even more flexibility with its dimming capabilities. Featuring a 1" slim line design with warm color tones designed to enhance any application, the NUC-3 offers improved temperature consistency and a specially designed diffuser that eliminates hot spots on counter surfaces. Available in five lengths and in four decorative colors, the NUC-3's cool operating temperature and warm natural color makes this energy efficient fixture a great choice for accent, office, cove, task and display lighting.

Construction

Low profile aluminum housing, with on/off rocker switch, available in either White, Oil-Rubbed Bronze, Black, or Nickel

Optical System

Even lighting with specially designed diffuser to prevent "hot spots" on counter tops

Electrical

Greater than 90 CRI
 Utilizes high performing LEDs
 Dimmable with most Triac dimmers
 Custom low-profile driver engineered for optimal dimming across all sizes
 Operating temperature rating of 0°F to 120°F (-18°C – 49°C)
 120V line voltage no transformer
 L70 rated for greater than 60,000 hours
 TM-21 Projected L70(10k) life >96,000 hours
 LM-79, LM-80 testing performed in accordance with IESNA standards

Finish

Available in 4 color options: White, Nickel, Oil-Rubbed Bronze, & Black

Installation

Easy surface mount installation

Warranty

5-year limited system warranty standard

Product Information

Color Temperature: 2700 K

LED Lifetime (Hrs): >60,000

Dimensions: Height: 1" Width: 3 1/2" Length: Varies

| Power Draw (W): | Length | Power(W) | Lumens: | Length | Lumens |
|---|---------|----------|---|---------|--------|
| Varies based on length and output selection | 8" | 3.16W | Varies based on length and output selection | 8" | 202 |
| | 12 1/2" | 5.23W | | 12 1/2" | 332 |
| | 21 1/2" | 7.72W | | 21 1/2" | 484 |
| | 30" | 10.72W | | 30" | 690 |
| | 40" | 14.06W | | 40" | 917 |



Ordering Information

| Series | Length | Housing Color |
|--------|--------------------|------------------------|
| NUC-3 | 08 (8 inches) | BK (black) |
| | 12 (12 1/2 inches) | NK (nickel) |
| | 21 (21 1/2 inches) | OB (oil-rubbed bronze) |
| | 30 (30 inches) | WH (white) |
| | 40 (40 Inches) | |