

| Project | Comments | |
|-----------|----------------|--|
| Catalog # | Prepared By | |
| Туре | Date | |

DESCRIPTION

- · Suitable for new construction in residential and commercial applications.
- · IC rated. Suitable for direct contact with insulation.
- Use one 18W double twin tube, G24Q-1 (not included).

HOUSING


- Washington State Energy Code approved to meet restricted airflow requirements.
- Airtight housing limits the exchange of air between ceiling plenum and heated/ cooled areas.
- Ballast includes integral thermal protector and guards against improper lamp
- installation and misuse of insulation materials.
- 120-277V Universal input electronic ballast.
- 6 1/4" height allows use in 2" x 6" joist construction.


JUNCTION BOX

- · Listed for through branch circuit wiring and includes several 3/4" knockouts.
- Supplied with three IDEAL® push-in wire connectors.

LISTINGS

- UL damp location
- UL feed-through
- CUL











| | Order No | Description | Maximum Lamp Rating | |
|--|--------------|----------------------------------|------------------------------|-----------------|
| | | Specular Cone | 1x13W ¦ G24Q-1 | 2 1/4" |
| | 19503 | Gold (shown) | OD: 5" | |
| | 19503WHZ-ABZ | Wheat Haze (Aged Bronze Ring) | | 3 1/2* |
| | | | | |
| | Order No | Description | Maximum Lamp Rating | |
| | | Specular Cone | 1x13W ¦ G24Q-1 | |
| | 19504 | Clear | OD: 5" | |
| | | | | 5" |
| _ | Order No | Description | Maximum Lamp | |
| | | Description | Maximum Lamp Rating | |
| and the second sec | | Albalite Shower | 1x13W ¦ G24Q-1 | |
| | 19509BK | Black | OD: 5" GE F13BX/835/A/ECO | 3 1/2" 5" |
| | 19509BZ | Bronze | is recommended | |
| | 19509CL | Clear | | |
| | 19509OB | Oil-Rubbed Bronze | Wet Location Rated | |
| | 19509WH | White | | |
| | Order No | Description | Maximum Lamp Rating | |
| | | Drop Opal Shower | 1x13W ¦ G24Q-1 | |
| | 19510CL | Clear | OD: 5" | 3" |
| | 19510GD | Gold (shown) | Wet Location Rated | 3 1/2" 5" |
| | 19510WH | White | | |
| | Order No | Description | Maximum Lamp | ⊨ 2 7/10* ⊣ |
| | | | Rating | |
| | | Specular Cone | 1x26W ¦ G24Q-3 | |
| | 19552CL | Clear | OD: 4" | |
| | 19552MT | Matte | | 3 1/2" |
| | | | | 5* |
| | Order No | Description | Maximum Lamp Rating | 2 7/10" - |
| Constanting of the second | | Albalite Shower | 1x26W ¦ G24Q-3 | 5 |
| | 19555CL | Clear | OD: 4" | 2 1/5" P |
| | 19555MT | Matte | | |
| | | | | 5° |

14306AREBM18 Double Twin 4" Fluorescent Remodel Compact Housing



| | Order No | Description | Maximum Lamp Rating | |
|--|-----------|---|--------------------------|-----------|
| | | Baffle | 1x26W ¦ G24Q-3 OD: 4" | |
| | 19550BK | Black | | |
| | 19550NK | Brushed Nickel | | |
| | 19550OB | Oil-Rubbed Bronze | | |
| | 19550WH | White (shown) | | |
| | | | · | |
| | Order No | Description | Maximum Lamp Rating | 2 7/10* - |
| | | Baffle | 1x26W G24Q-3 OD: 4" | |
| | 19550BKCL | Black Baffle/Clear | | |
| | 19550NKCL | Brushed Nickel Baffle/ Clear | | |
| | 19550OBCL | Oil-Rubbed Bronze Baffle/Clear (shown) | | |
| | 19550WHCL | White Baffle/Clear | | |